

# **Technical Specifications**

### **Vaxtor Container Code Recognition App**

#### Recognition of cargo container codes according to ISO 6346

Based on deep learning processes the certified Vaxtor Container Code Recognition App recognizes container codes and delivers realtime results about the container owner, type dimensions and much more. The app is able to detect container codes within 900 ms and an extremely high hit probability of over 99 percent. Via blocking or permission lists, authorized, or containers with unauthorized content can be defined specifically. Possible areas of use for the application are harbor & airport logistics, container inventory & surveillance, border control, access control or logistic management.

- Recognition of cargo container codes according to ISO 6346 standard
- with over 99% accuracy optimally suited for detection and logging of container codes on entry, between zones, during processes or exit
- Two lists for individual actions (e.g. access granted/denied, alarm, etc.)
- Integrated Smart Data Interface for data retrieval with MxManagementCenter from version 2.4.3.





### **Technical Specifications**

## **Vaxtor Container Code Recognition App**

### **Product Information**

| Product Name           | Vaxtor Container Code Recognition App |
|------------------------|---------------------------------------|
| Order Code             | Mx-APP-VX-CON                         |
| Supported MOBOTIX Cam- | Mx-M73A, Mx-S74A                      |
| eras                   |                                       |

| eras                              |  |  |
|-----------------------------------|--|--|
| Minimum Camera Firmware v7.1.3.x  |  |  |
| MxManagementCenter<br>Integration | <ul> <li>min. MxMC v2.4.3</li> <li>Configuration: Advanced Config license required</li> <li>Event Search: Smart Data Interface license included</li> </ul> |  |
|                                   |  |  |

### **Product Features**

| App Features               | <ul> <li>Recognition of cargo container codes according to ISO 6346</li> </ul> |
|----------------------------|--|
|                            | Real time results:   |
|                            | <ul><li>Container Code</li></ul>   |
|                            | <ul> <li>Owner and corresponding origin</li> </ul>                             |
|                            | <ul><li>Container Type</li></ul>   |
|                            | <ul><li>Container Dimensions</li></ul>   |
|                            | <ul><li>Control Digit</li></ul>  |
|                            | Control Digit Validation   |
|                            | ■ Recognition log (Smart Data / Event Search via MxManagementCenter)           |
|                            | ■ MOBOTIX events via MxMessageSystem   |
|                            | Two lists for individual actions (e.g. access granted/denied, alarm, etc.)     |
|                            | ■ Free flow and Signaled mode  |
| Maximum number of recog- 1 |  |

| nition areas                              |               |
|---|---------------|
| Maximum number of enrolled license plates | 1000 per list |
| Meta Data / Statistic formats             | JSON          |

| Trial License                  | 30-day trial license pre-installed  |
|--------------------------------|---|
| MxMessageSystem sup-<br>ported | Yes   |
| Integration Interfaces         | <ul> <li>MxMC Smart Data</li> <li>IP Notification</li> <li>Milestone X-Protect</li> <li>MOBOTIX SYNC</li> <li>generic 3rd party integration via XML</li> <li>compare supported camera's interfaces</li> </ul> |
| MOBOTIX Events                 | Yes   |
| ONVIF Events                   | Yes (Generic Message event)   |

### **Supported Container Codes**

Supported Container Codes Container code specification according to ISO 6346

### **Scene Requirements**

| Character Height         | 20px - 50px |
|--------------------------|-------------|
| Maximum Vertical Angle   | 30°         |
| Maximum Horizontal Angle | < 25°       |
| Maximum Tilt Angle       | < 25°       |

### **Technical App Specifications**

| Synchronous / Asyn-<br>chronous App  | asynchronous                              |
|--------------------------------------|---|
| Simultaneous execution of other apps | No  |
| Accuracy                             | min. 99% (considering scene requirements) |
| Processed frame rate                 | typ. 10 fps                               |
| Detection time                       | typ. 900 ms per Container                 |

