

Technical Specifications

Vaxtor Aircraft Identification Number Recognition App

Recognition of ICAO- and FAA-issued identification numbers (AIN)

The certified Vaxtor Aircraft Identification Number Recognition App recognizes, based on deep learning processes AIN codes (Aircraft Identification Number) which adhere to the International standard. The OCR engine takes advantage of many current integrations and publishing capabilities that have been developed over many years.

- Recognition of ICAO- and FAA-issued identification numbers
- Identification and tracking in real-time during parking, take-off and landing
- Infrastructure expansion possible without having to interfere with existing air traffic processes and operations
- MOBOTIX events via MxMessageSystem
- Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB
- meta data transfer through generic transmission protocols and / or pre-defined 3rd party interfaces
- Two lists for individual actions (e.g. access granted/denied, alarm, etc.)

HEVCAdvance™

MOBOTIX

Beyond Human Vision

Product Information

Product Name	Vaxtor Aircraft Identification Number Recognition App	
Order Code	Mx-APP-VX-AIN	
Supported MOBOTIX Cam- eras	Mx-M73A, Mx-S74A	
Minimum Camera Firmware v7.3.0.x		
MxManagementCenter com patibility	 min. MxMC v2.5.3 Configuration: Advanced Config license required Event Search: Smart Data Interface license included 	
MOBOTIX HUB com- patibility.	 min. MOBOTIX HUB version: 2021 R1 min. MOBOTIX HUB license level (Analytics Events): L2 min. MOBOTIX HUB license level for Event Search Plug-In: L4 	

Product Features

App Features	 Recognition of ICAO- and FAA-issued identification numbers Operations up to a speed of 50 km/h Recognition log (Smart Data / Event Search via MxManagementCenter) MOBOTIX events via MxMessageSystem Two lists for individual actions (e.g. access granted/denied, alarm, etc.) Free flow and Signaled mode
Maximum number of recog- nition areas	1
Maximum number of enrolled AIN codes	5000 per list
Meta Data / Statistic formats	JSON, XML
Trial License	30-day trial license pre-installed
MxMessageSystem sup- ported	Yes
Integration Interfaces	MxMC Smart Data

	 IP Notification Milestone X-Protect (Analytics Events, Transmission Plug-In) Network Optix NxWitness MOBOTIX SYNC Genetec Security Center (Custom Events, Bookmarks) generic 3rd party integration through FTP and / or XML / JSON via HTTP(S) compare supported camera's interfaces
MOBOTIX Events	Yes
ONVIF Events	Yes (Generic Message event)

Supported Aircraft Identification Numbers

Supported Aircraft Iden-	ICAO- and FAA-issued identification numbers
tification Numbers	

Scene Requirements

Character Height	20px - 50px
Maximum Vertical Angle	30°
Maximum Horizontal Angle	< 25°
Maximum Tilt Angle	< 25°

Technical App Specifications

Synchronous / Asyn- chronous App	asynchronous
Simultaneous execution of other apps	No
Accuracy	min. 99% (considering scene requirements)
Processed frame rate	typ. 10 fps
Detection time	typ. 300 ms per number



EN_02/25 MOBOTIX AG • Kaiserstrasse • D-67722 Langmeil • Tel.: +49 6302 9816-103 • sales@mobotix.com • www.mobotix.com MOBOTIX is a trademark of MOBOTIX AG registered in the European Union, the U.S.A., and in other countries. Subject to change without notice. MOBOTIX do not assume any liability for technical or editorial errors or omissions contained herein. All rights reserved. © MOBOTIX