

Technical Specifications

Vaxtor UIC - Railway Code Recognition App

Recognition of International Union of Railways Wagon and Coach Numbers (UIC)

The certified Vaxtor UIC - Railway Code Recognition App recognizes, based on deep learning processes UIC codes (International Union of Railways Wagon and coach numbers) which adhere to the International standard. The OCR engine takes advantage of many current integrations and publishing capabilities that have been developed over many years.

- Recognition of the UIC Codes
- Real time results for UIC Code, Country Code, Vehicle Type, Control Digit, Direction of travel
- Stop / Go and slow speed (<10 km/h) applications (depending on installation and module selection)
- MOBOTIX events via MxMessageSystem
- Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB
- meta data transfer through generic transmission protocols and / or pre-defined 3rd party interfaces
- Two lists for individual actions (e.g. access granted/denied, alarm, etc.)
- Free flow and signaled mode

HEVCAdvance™

MOBOTIX

Technical Specifications

Vaxtor UIC - Railway Code Recognition App

Product Information

Product Name	Vaxtor UIC - Railway Code Recognition App	
Order Code	Mx-APP-VX-UIC	
Supported MOBOTIX Cameras	Mx-M73A, Mx-S74A	
Minimum Camera Firmware v7.1.4.x		
MxManagementCenter compatibility	 Configuration: Advanced Config license required 	
	 Event Search: Smart Data Interface license included 	
MOBOTIX HUB compatibility.	 min. MOBOTIX HUB version: 2020 R3 min. MOBOTIX HUB license level (Analytics Events): L2 min. MOBOTIX HUB license level for Event Search Plug-In: L4 	

Product Features

Maximum number of

enrolled UIC codes

5000 per list

App Features	 Recognition of cargo container codes according to ISO 6346 Real time results: Container Code Owner and corresponding origin Container Type Container Dimensions Control Digit Control Digit Validation Recognition log (Smart Data / Event Search via MxManagementCenter) MOBOTIX events via MxMessageSystem Two lists for individual actions (e.g. access granted/denied, alarm, etc.) Free flow and Signaled mode
Maximum number of recog- 1 nition areas	

Meta Data / Statistic formats	JSON, XML
Trial License	30-day trial license pre-installed
MxMessageSystem sup- ported	Yes
Integration Interfaces	MxMC Smart Data
	■ IP Notification
	Milestone X-Protect (Analytics Events, Transmission Plug-In)
	■ MOBOTIX SYNC
	Genetec Security Center (Custom Events, Bookmarks)
	generic 3rd party integration through
	FTP and / or XML / JSON via HTTP(S)
	compare supported camera's interfaces
MOBOTIX Events	Yes
ONVIF Events	Yes (Generic Message event)

Supported Railway Codes

Supported Railway Codes	Wagon numbers / codes according to the specification of the International
	Union of Railways

Scene Requirements

Character Height	20px - 50px
Maximum Vertical Angle	30°
Maximum Horizontal Angle	< 25°
Maximum Tilt Angle	< 25°

Technical App Specifications

Synchronous / Asyn-	asynchronous
chronous App	
Simultaneous execution of	No

Technical Specifications

Vaxtor UIC - Railway Code Recognition App

other	apps
Othici	apps

Accuracy	min. 99% (considering scene requirements)
Processed frame rate	typ. 2 fps
Detection time	typ. 900 ms per wagon

